

ROMPACT 30.10 Portable Impact Wrench

For tightening and loosening nuts and sleeper and fishplate bolts.

THE ADVANTAGES. YOUR BENEFITS.

Compact and robust

- Centrifugal clutch and change gear
- 1-inch square drive

Ergonomic and flexible

- Adjustable speed
- Low-vibration operation



ROMPACT 30.10 - 8359900006

SPECIFICATION

Drive	2-stroke petrol engine	2-stroke petrol engine
Output	1.57 kW	1.57 kW
Max. torque	1700 Nm, depending on joint stiffness	1700 Nm, depending on joint hardness
Vibration damping	No	Yes
Dimensions (L x W x H)	680 x 390 x 360 mm	700 x 390 x 360 mm
Total weight	from 19.8 kg	from 21.6 kg
Socket weight	from 1.5 kg	from 1.5 kg

ACCESSORIES

Sockets

Other sockets available on request.

Hexagonal

- 9871033313 AF 30
- 9871033309 AF 32
- 9002501223 AF 34
- 9871033314 AF 35
- 9871033311 AF 36
- 9871033315 AF 38
- 8098950100 AF 39 Special 230 mm
- 9871033391 AF39
- 9871033304 AF 41
- 9871033308 AF 42
- 9002501224 AF 46

Rectangular

- 9871033317 rect. 18 x 26
- 9800308006 rect. 20,5 x 24,5
- 9871033302 rect. 21 x 28
- 9871033305 rect. 30 x 22

Square

- 9871033303 SQ 19 x 19/17 x 17
- 9871033318 SQ 21 x 21
- 9871033306 SQ 22 x 22
- 9871033319 SQ 24 x 24

Drill adapter/drill bit

Other drill bits available on request.

- 8099910001 SDS Plus chuck adapter



Sleeper drill bits

Max. drilling depth 150 mm with SDS Plus adapter

- 9002501808 Ø 14 mm
- 9002501809 Ø 16 mm
- 9002501810 Ø 18 mm
- 9002501811 Ø 20 mm
- 9002501812 Ø 22 mm

Miscellaneous

- 8003009006 Extension 180 mm/1" adapter
- 8003009005 Extension 330 mm/1" adapter
- 8003009007 Cardan joint 1" adapter
- 9909992145 O-ring, circlip to secure socket
- 9900070056 Cylindrical pin Ø 6 mm to secure socket

